



PALLET TRUCK/FORKLIFT STANDARD

MINIMIZE DOWNTIME. MAXIMIZE SAFETY.

Fires cause costly damage and downtime in warehouses, ports, and factories, while smoke alone can destroy valuable stock. The Bridgehill Forklift Fire Blanket isolates flames, smoke, and toxic fumes in seconds.

Key Benefits

- Protects goods, buildings, and operations, minimizing downtime
- Controls forklift- and pallet truck fires within seconds
- Efficiently isolates fires in both conventional and electric battery-powered forklifts- and pallet trucks
- Immediately contains toxic gases and smoke, reducing carcinogen exposure
- Ideal for high-risk environments such as warehouses, ports, factories, and manufacturing sites



Product Features

- Equipped with eyelets along the edge, allowing secure fastening or safe deployment with Bridgehill Extendable Poles
- Delivered in a compact, portable smartbag
- Available in two sizes to match standard forklifts and pallet trucks
- Optimized for rapid deployment in confined spaces
- NFPA 701-2019 *
- EN ISO 1182 on core fabric
- EN ISO 1716 on core fabric
- EN 13501-1: Reaction to fire classification A1 on core fabric
- Surface and volume resistivity in accordance with ASTM D257 *

Size/Weight Forklift Standard:

± 7 × 7 m Weight ± 25 kg
± 23 × 23 ft Weight ± 55.12 lb

Size/Weight Pallet Truck:

± 5 × 5 m Weight ± 12 kg
± 16.40 × 16.40 ft Weight 26.46 lb



For instruction videos
scan QR code

Smartbag:

Included with every blanket for safe storage, easy transport, and long-term usability.

- Airtight
- Equipped with shoulder straps and handles for easy transport
- Includes instruction manual in four languages
- Comes with a repair kit for patching holes caused by sharp objects
- EN 60529: 1991 (Conformity with IP65)



* Test was performed on the material system consisting of pyroxene fabric with BridgeTech™ polymer coating.



PALLET TRUCK/FORKLIFT STANDARD

TECHNICAL SHEET

SKU	Pallet Truck: New SKU 20010103 (replaces SKU 211227) Forklift Standard: New SKU 20010104 (replaces SKU 201252)
HS Code	68159990
Size/Weight	Pallet Truck: $\leq 5\% 5 \times 5 \text{ m} \pm 12 \text{ kg} \leq 5\% 16.40 \times 16.40 \text{ ft} \pm 26.46 \text{ lb}$ Forklift Standard: $\leq 5\% 7 \times 7 \text{ m} \pm 25 \text{ kg} \leq 5\% 23 \times 23 \text{ ft} \pm 55.12 \text{ lb}$
Coating and Core Material	BridgeTech™ polymer coating and pyroxene
Total gsm	$\pm 430 \text{ gsm}$
Blanket Edge	Equipped with eyelets at one-meter intervals along the edges
Main Usage	<ul style="list-style-type: none"> Conventional forklifts- and pallet trucks Electric forklifts- and pallet trucks
Smartbag	<ul style="list-style-type: none"> Delivered in an airtight smartbag with shoulder straps and handles for easy transport by one or two people Zipper maintenance: Apply included silicone grease to preserve airtightness
Shelf Life	10 years shelf life. Annual visual inspection is recommended
Disposal Guidelines	Check Local Regulations
Service temperature on core fabric	Short term $\pm 1600 \text{ }^{\circ}\text{C} \pm 2912 \text{ }^{\circ}\text{F}$ Long term $\pm 800 \text{ }^{\circ}\text{C} \pm 1472 \text{ }^{\circ}\text{F}$

SAFETY NOTICE

May generate static electricity from friction during use.

Not designed to protect against electric shock.

Permeable to radio frequencies.

Avoid use near flammable gases or sensitive electronic equipment.